



**Kawasaki ZX6RR  
Fender Eliminator Kit  
P/N: 670-4410**


Kit Contents

Part Number	Description	Quantity
99-FE-670-4410	2 Pc. Bracket	1
99-FE-HST12	Heat Shrink	12"
99-HB-6x12	6x12 Bolt	2
99-Wash6x15	6x15mm Washer	2
99-Wash6x12	6x12mm Washer	2
99-LN-6	6mm Lock nut	2


- 1 - Remove both Seats.
- 2 - Disconnect brake light wire, marker light wires and license plate light wire from under seat. (may need to remove rear bodywork for easy access).
- 3 - Remove small trim piece above tail light, by pushing in 2 plastic rivets.
- 4 - Remove marker lights (3 Allen bolts from both sides). (fig.1)
- 5 - Remove stock marker light mounts (2 Allen both sides). (Fig. 2)
- 6 – Remove rear fender from exhaust. (4 – 10mm bolts).
- 7 – Remove Tail light from rear fender,
- 8 – Remove bracket from tail light.
- 9 – Mount brake light and marker lights to DMP Fender Eliminator. (Recommend using DMP marker lights).
- 10 - Route wires thru main pan. Caution: Use heat shrink over wires and secure wires away from exhaust. (Recommend using DMP wire extensions and DMP stock type wire harness).
- 11 – Mount light and license plate to license pan.
- 12 – Mount license pan & tail light to main pain, using stock tail light screws.
- 13 – Mount DMP Fender Eliminator to motorcycle using the factory 6mm x 12 hex flange bolts. Secure wires away from exhaust.
- 14- Connect brake light wire, marker light wires and license plate wire. (Plate light not included) Caution: Route wires under left rear bodywork using stock wire clips. Secure wires away from exhaust
- 15 – Check lighting for proper function.
- 16 – Mount rear bodywork if previously removed.
- 17 – Mount seats and side covers.
- 18 - Remaining hardware to be used for mounting license plate.



**Kawasaki ZX6RR 07-08**  
**Fender Eliminator Kit**  
**P/N: 670-4410**



**Fig. 1**



**Fig. 2**



Note: To complete your installation we recommend using DMP Marker Lights and DMP OEM Type Wire Harness, which are available from your local DMP dealer or [www.moto911.com](http://www.moto911.com).

Use blue thread locker to secure bolts. Refer to owner's manual for proper torques.