

## **GSXR1000** Fender Eliminator Kit

P/N: 670-5320

## Kit Contents

Part Number	Description	Quantity
99-FE-670-5320	Fender Brackets	1
99-HB-6x30	6x30 Bolt	4
99-HB-6x12	6x12 Bolt	6
99-Wash6x15	6x15mm Washer	10
99-Wash6x12	6x12mm Washer	6
99-LN-6	6MM Lock Nuts	6

- 1 Remove passenger seat.
- 2 Disconnect license plate light wire (black wrapped wire).
- 3 Remove factory fender by removing (4) 6mm hex flange bolts from under tail.
- 4 Mount the "DMP Fender Eliminator Kit" side brackets loosely with (4) supplied 6x30mm bolts and (4) 6x15mm washers. (Do not tighten at this time)
- 5 FIRST Mount plate bracket using (2) supplied 6x12mm button head bolts, (2) 6x12mm washers, and locknuts. Center the plate and brackets on tail section and tighten the (2) 6x12mm plate bracket bolts and (4) 6x30mm side bracket bolts.
- 6 Connect license plate light wire to aftermarket license plate light (not included/optional) and check for proper function.
- 7 Reinstall passenger seat.
- 8- Remaining hardware to be used for mounting license plate.

Use blue thread locker to secure bolts. Refer to owner's manual for proper torques.

