



**Yamaha R6  
Yamaha R6S  
Fender Eliminator Kit  
P/N: 670-6300**

Kit Contents

Part Number	Description	Quantity
99-FE-670-6300	Fender Bracket	1
99-Wash6x15	6x15mm Washer	8
99-LN-6	6mm Lock Nuts	8
99-HB-6x20	6x20 Bolt	4
99-HB-6x12	6x12 Bolt	4
99-Wash6x12	6x12mm Washer	4

- 1 - Remove rear Seat.
- 2 - Disconnect (2) wires from the marker lights and (1) wire from the License Plate light.
- 3 – Remove (4) stock fender bolts. Remove fender by gently pulling wires and fender down towards tire. (Fig.1)
- 4 – Mount “DMP Fender Eliminator Kit” by using the provided 6MM bolts with supplied washers and lock nuts. Torque bolts as necessary.
- 5 - Connect License Plate light and marker lights (not included), then check for proper function.
- 6 – Re-install Rear Seat.
- 7- Remaining hardware to be used for mounting license plate.

Note: To complete your installation we recommend using DMP Marker Lights and DMP OEM Type Wire Harness, which are available from your local DMP dealer or [www.moto911.com](http://www.moto911.com).

Use blue thread locker to secure bolts. Refer to owner’s manual for proper torques.



Fig 1