



**CBR600RR NO CUT Frame Slider Installation
Instructions**
**Part Numbers: 755-3319, 750-3319, 750-3310,
850-3310**

MADE IN THE USA!

Carefully read instructions in their entirety before the install

Professional installation is recommended. Always use proper safety measures during the install of this product. Do not try to install this product without proper tools, recently calibrated torque wrench, correct torque specifications from **factory service manual**, safety goggles and gloves. The motorcycle must be in a fixed secure position before the install process begins. **DO NOT** remove both engine studs at the same time. **Shogun is not responsible for any part of your motorcycle for any reason.** Precisely measure location of cut and if in doubt at any point please call us before the install process has begun.

Replacement Parts List: Left Side Components (as if you were sitting on the bike)

QTY	Price each	Part Numbers	Descriptions
1	\$20.00	99-FS-750-3319-L	Black Left Side Puck
1	\$20.00	99-FS-750-3310-L	White Left Side Puck
1	\$30.00	99-FS-850-3310-L	Polished Billet Left Side Puck
1	\$40.00	99-OF-750-3310-L	Left Side Offset Black Anodized
1	\$3.50	99-HB-SH10125080	Socket Cap 10 X 1.25 X 80 (Holds puck to offset)

Replacement Parts List: Right Side Components (as if you were sitting on the bike)



1	\$20.00	99-FS-750-3319-R	Black Right Side Puck
1	\$20.00	99-FS-750-3319-R	White Right Side Puck
1	\$30.00	99-FS-850-3310-R	Polished Billet Right Side Puck
1	\$40.00	99-OF-750-3310-R	Right Side Offset Black Anodized
1	\$3.50	99-HB-SH10125070	Socket Cap 10 X 1.25 X 70 (Holds puck to offset)

Frame Sliders: Left side slider longer than right.

Installation Steps:

Some photos in this section are used for illustration examples only.

1. Remove lower panel to expose mounting locations.
2. Remove left engine stud. There is a spacer that is located between the frame and the engine. Your left side offset will mount in this location.



3. Mount the left side offset using the stock OEM 12mm Hex Flange bolt. Make sure that the wire loom is routed properly and not being pinched by the offset in anyway. Line up the edge of the offset (wile mounted) with the edge of the frame and torque down.




4. Use one drop of blue thread locker on the (99-HB-SH10125080) Socket Cap 10 X 1.25 X 80 (Holds puck to offset). Torque down to 30 to 32 foot lbs.



5. Remove right engine stud. There is a spacer that is located between the frame and the engine. Your right side offset will mount in this location. The zip tie located around the spacer is reusable, simply unlock it by hand so you can reuse later.



6. Mount the right side offset using the stock OEM 12mm Hex Flange bolt. Make sure that the wire loom is routed properly and not being pinched by the offset in anyway. Line up the edge of the offset (wile mounted) with the edge of the frame and torque down.



7. Use one drop of blue thread locker on the (99-HB-SH10125070) Socket Cap 10 X 1.25 X 70 (Holds puck to offset). Torque down to 30 to 32 foot lbs.



8. Remount lower panel.

READ CAREFULLY

Shogun cannot guarantee that they will protect your motorcycle from any extent of damage. Shogun frame sliders are really meant to help possibly save the frame from damage in the event of a crash. Because Shogun frame slider products have been very successful in saving cases, bodywork, levers and so on in the past, customers just assume sometimes you can put the product on and no damage will happen. The fact is, some crashes result in little or no damage to the motorcycle and some bikes are destroyed. It's kind of like a bumper on a car sometimes it works sometimes it doesn't, it really depends on all the different forces applied during the incident. We've seen bikes crash at 100 mph with little damage and some at 15 mph with major damage.