



**Yamaha FZ09 2017 MT-09 2018 2019 No Cut
Frame Slider
Installation Instructions
Part Numbers: 750-6429, 755-6429, 750-6429,
710-6429**

MADE IN THE USA!

Carefully read instructions in their entirety before the install

Professional installation is recommended. Always use proper safety measures during the install of this product. Do not try to install this product without proper tools, recently calibrated torque wrench, correct torque specifications from **factory service manual**, safety goggles and gloves. The motorcycle must be in a fixed secure position before the install process begins. **DO NOT** remove both engine studs at the same time. **Shogun is not responsible for any part of your motorcycle for any reason.** Precisely measure location of cut and if in doubt at any point please call us before the install process has begun.

Replacement Parts List: Left Side Components (as if you were sitting on the bike)

QTY	Price each	Part Numbers	Descriptions
1	\$20.00	99-FS-750-6429-L	Black Left Side Puck
1	\$20.00	99-FS-750-6420-L	White Left Side Puck
1	\$25.00	99-FS-715-6429-L	PA2 Left Side Puck
1	\$35.00	99-OF-750-6420-L	Left Side Offset Black Anodized
1	\$2.50	99-HB-SH1015045	Socket Cap 10 X 1.5 X 45 (Holds puck to offset)
1	\$3.50	99-HB-SH10125070	Socket Cap 10 X 1.25 X 70 Main Engine Stud

Replacement Parts List: Right Side Components (as if you were sitting on the bike)

1	\$20.00	99-FS-750-6429-R	Black Right Side Puck
1	\$20.00	99-FS-750-6420-R	White Right Side Puck
1	\$25.00	99-FS-715-6429-R	PA2 Right Side Puck
1	\$35.00	99-OF-750-6420-R	Right Side Offset Black Anodized
1	\$2.50	99-HB-SH1015045	Socket Cap 10 X 1.5 X 45 (Holds puck to offset)
1	\$3.50	99-HB-SH10125070	Socket Cap 10 X 1.25 X 70 Main Engine Stud

Frame Sliders as if you were sitting on the bike: Left side puck longer than right. Offsets are the same left and right.

Installation Steps:

1. Remove left main engine stud. Mount left side offset, orientate offset as shown in the picture below. Using (99-HB-SH10125070) Socket Cap 10 X 1.25 X 70 Main Engine Stud mount offset and torque down to OEM specs. Mount left side frame slider utilizing (99-HB-SH1015045) Socket Cap 10 X 1.5 X 45 (Holds puck to offset) and torque down to 32 FT lbs.



2. Remove right main engine stud. Mount right side offset, orientate offset as shown in the picture below. Using (99-HB-SH10125070) Socket Cap 10 X 1.25 X 70 Main Engine Stud mount offset and torque down to OEM specs. Mount right side frame slider utilizing (99-HB-SH1015045) Socket Cap 10 X 1.5 X 45 (Holds puck to offset) and torque down to 32 FT lbs.



READ CAREFULLY

Shogun cannot guarantee that they will protect your motorcycle from any extent of damage. Shogun frame sliders are really meant to help possibly save the frame from damage in the event of a crash. Because Shogun frame slider products have been very successful in saving cases, bodywork, levers and so on in the past, customers just assume sometimes you can put the product on and no damage will happen. The fact is, some crashes result in little or no damage to the motorcycle and some bikes are destroyed. It's kind of like a bumper on a car sometimes it works sometimes it doesn't, it really depends on all the different forces applied during the incident. We've seen bikes crash at 100 mph with little damage and some at 15 mph with major damage.